

Aircraft Corporation “Rubin”

Russian Federation, 143900, Balashikha, Moscovskaya oblast, Zapadnaya Promzona, Shosse Entuziastov, 5

Phone: (495) 521-50-65, Fax: (495) 521-53-11, E-mail: commerce@ak-rubin.ru

HYDRAULIC DISTIBUTORS WITH ELECTOMAGNETIC CONTROL

| Product code | Pressure, kgf/sm ² | | Operating liquid | | Hydraulic resistance of each branch (+20 °C) | | Electrical power DC | | Mass, kg, not more |
|-----------------|-------------------------------|----------|------------------|-----------------------|--|------------------------------------|---------------------|-------------------------------|--------------------|
| | Rating | Inlet | Type | Temperature range, °C | At rate, l/min | ΔP, kgf/sm ² , not more | Rating voltage, V | Consumed current, A, not more | |
| KE50-8 | 280 | 30...280 | AMG-10 | -60...+120 | 40/20 | 8/15 | 27 | 1.0 | 1.6 |
| KE53-8 | 280 | 30...280 | AMG-10 | -60...+125 | 50 | 12 | 27 | 1.0 | 2.4 |
| KE68 | 210 | 0...220 | NGZH-5U | -55...+100 | 6 | 8 | 27 | 2.3 | 1.2 |
| KE68-2 | 210 | 0...220 | AMG-10 | -60...+125 | 5 | 8 | 27 | 2.3 | 1.2 |
| KE70 | 210 | 30...220 | NGZH-5U | -55...+100 | 80 | 5 | 27 | 1.2 | 1.9 |
| KE71 | 210 | 30...220 | NGZH-5U | -55...+100 | 25 | 3.5 | 27 | 1.2 | 1.3 |
| KE71-2 | 210 | 30...220 | AMG-10 | -60...+100 | 25 | 3.5 | 27 | 1.2 | 1.3 |
| KE72, KE72-3 | 210 | 30...220 | NGZH-5U | -55...+100 | 40 | 5 | 27 | 1.2 | 0.95 |
| KE72, KE72-4 | 210 | 30...220 | AMG-10 | -60...+100 | 40 | 5 | 27 | 1.2 | 0.95 |

Operating mode of electromagnets permits additional switch.
Application of other types of liquids is discussed additionally.

| Product code | Pressure, kgf/sm ² | | Operating liquid | | Hydraulic resistance of each branch (+20 °C) | | Electrical power DC | | Mass, kg, not more |
|--------------|-------------------------------|----------|------------------|-----------------------|--|------------------------------------|---------------------|-------------------------------|--------------------|
| | Rating | Inlet | Type | Temperature range, °C | At rate, l/min | ΔP, kgf/sm ² , not more | Rating voltage, V | Consumed current, A, not more | |
| KE74, KE74-4 | 210 | 30...220 | NGZH-5U | -55...+100 | 10 | 5 | 27 | 12 | 0.6 |
| KE74-2 | 210 | 30...220 | AMG-10 | -60...+100 | 10 | 5 | 27 | 1.2 | 0.6 |
| KE75 | 210 | 0...220 | NGZH-5U | -55...+80 | 25 | 9 | 27 | 1.2 | 0.99 |
| KE75-2 | 210 | 0...220 | AMG-10 | -60...+100 | 25 | 9 | 27 | 1.2 | 0.99 |
| KE90 | 55 | 3...55 | AMG-10 | -60...+65 | 2.7 | 2 | 13.5 | 0.6 | 0.23 |
| KE91 | 210 | 0...220 | AMG-10 | -60...+100 | 5 | 5 | 27 | 1.2 | 0.85 |
| KE92 | 210 | 30...220 | AMG-10 | -60...+100 | 10 | 5 | 27 | 1.2 | 0.42 |
| KE93 | 210 | 0...220 | AMG-10 | -60...+100 | 5 | 7 | 27 | 1.1 | 0.9 |
| KE94 | 210 | 30...220 | AMG-10 | -60...+100 | 10 | 5 | 27 | 1.2 | 0.4 |
| KE94-2 | 210 | 30...220 | NGZH-5U | -55...+100 | 10 | 5 | 27 | 1.2 | 0.4 |
| KE95 | 210 | 30...220 | AMG-10 | -60...+100 | 15 | 16 | 27 | 1.2 | 0.45 |
| KE95-2 | 210 | 30...220 | NGZH-5U | -55...+100 | 15 | 16 | 27 | 1.2 | 0.45 |
| KE100 | 210...350 | 80...350 | 7-50s-3 | -60...+150 | 100 | 5/90 | 27 | 1.2 | 14 |
| KE101 | 210...350 | 80...350 | 7-50s-3 | -60...+150 | 20 | 5/50 | 27 | 1.2 | 0.8 |
| KE105 | 210...350 | 80...350 | 7-50s-3 | -60...+150 | 30 | 5 | 27 | 1.2 | 1.0 |

Operating mode of electromagnets permits additional switch.
Application of other types of liquids is discussed additionally.