

Aircraft Corporation “Rubin”

Russian Federation, 143900, Balashikha, Moscovskaya oblast, Zapadnaya Promzona, Shosse Entuziastov, 5

Phone: (495) 521-50-65, Fax: (495) 521-53-11, E-mail: commerce@ak-rubin.ru

BY-PASS VALVES

Designed to prevent system from the pressure exceeding the given by passing operating liquid to return line.

Product code	Rated operating pressure, kgf /sm ²	Operating liquid		Pressure, kgf/sm ²				Recommended flow, l/min	Mass, kg not more
		Type	Temperature range, °C	Valve opening pressure	Upkeeping pressure at the recommended flow	Valve closing pressure	In the return line, up to		
RD58	210	NGZH-5Y	-55...+90	240	260	220	30	25	0.15
RD58-2	150	AMG-10	-55...+90	180	200	160	10	25	0.15
RD58-3	210	AMG-10	-60...+125	240	260	220	30	40	0.15
RD58-4	150	AMG-10	-60...+90	170	200	155	10	21	0.15
RD58-6	70	AMG-10	-60...+80	70	75	50	-	15	0.15
RD58-7	210	AMG-10	-60...+80	150	160	125	-	2.5	0.15
RD58-8	210	AMG-10	-60...+80	210	220	185	-	2.5	0.15
RD58-9	150	NGZH-5U	-55...+125	180	200	160	10	25	0.15
RD58-10	10	NGZH-5	-55...+125	15	16	10	3	2.5	0.15
RD64	280	AMG-10	-60...+125	320	345	290	20	100	0.25
RD66	350	7-50s-3	-60...+150	370	395	350	20	60	0.20