

# Aircraft Corporation "Rubin"

Russian Federation, 143900, Balashikha, Moscovskaya oblast, Zapadnaya Promzona, Shosse Entuziastov, 5

Phone: (495) 521-50-65, Fax: (495) 521-53-11, E-mail: commerce@ak-rubin.ru

## INTENSIFIERS

Designed to prevent individual parts of hydrosystem from the pressure falling below the given value.

Product code	Rated operating pressure, kgf/sm <sup>2</sup>	Operating liquid		Pressure, kgf/sm <sup>2</sup>			Electrical power DC		Mass, kg not more	Hydraulic resistance		
		Type	Temperature range, °C	Valve closing pressure	Valve opening pressure	On return, up to	Voltage, V	Current, A		ΔP, kgf/sm <sup>2</sup>	At inlet pressure, kgf/sm <sup>2</sup>	At rate, l/min
RD35	210	AMG-10	-60...+100	170	185	30	27	1	3.5	6	200	200
RD36	210	AMG-10	-60...+100	150	165	30	27	1	3.5	6	180	200
RD46	210	NGZH-5Y	-55...+100	150	165	30	-	-	0.65	5	170	70
RD56	210	AMG-10	-60...+100	135	155	5.5 15	27	1.2	2.1	9	170	110
RD57	210	AMG-10	-60...+100	135	155	5.5 15	27	1.2	1.4	4	170	90
RD57-2	210	NGZH-5U	-54...+125	135	155	5.5 15	27	1.2	1.4	5	210	21
RD58-5	210	AMG-10	-54...+100	150	180	-	-	-	0.18	5	210	21